

Product Datasheet - 21806

Gadai
ID : 21806
Input power : 50W LED
Technical Description
K-Lite Post top luminaire. Symmetrical light distribution. Luminaire made of specially contoured spun aluminium top cover with gravity die cast aluminium decorative knob on top, Gravity die cast aluminium supporting arm integrated with decorative aluminium sheet. Gravity die-cast aluminium base suitable for mounting Ø76mm OD pipe. Prismatic polycarbonate diffuser. All external screws made of stainless steel. Protection class IP65. Mechanical resistance IK10. Pure polyester powder coated RAL9004 Black, RAL9007 Grey aluminium, RAL7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >88%, Power factor >0.95, THD <10%, Surge protection 6KV. Luminaire dimension : 435mm diameter x 932mm height. CE & BIS Certified. Inhouse NABL accredited lab.
Gadai
ID : 21806
Holder : E27
Technical Description
K-Lite Post top luminaire. Luminaire made of specially contoured spun aluminium top cover with gravity die cast aluminium decorative knob on top, Gravity die cast aluminium supporting arm integrated with decorative aluminium sheet. Gravity die-cast aluminium base suitable for mounting Ø76mm OD pipe. Prismatic polycarbonate diffuser. All external screws are made of stainless steel. Protection class IP65. Mechanical resistance IK10. Pure polyester powder coated RAL9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Prewired with E27 holder and suitable for operating on 240V, 50Hz single phase ac supply. Luminaire dimension : 435mm diameter x 932mm height.

Wattage:

CCT: 2700K,3000K,4000K,5700K

Optics:

Mounting: D3

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey