

## Product Datasheet - 22530

Cylin Midi  
ID : 22530  
Input power : 25W / 40W LED - Sym & 30W - Asy  
K-Lite ceiling mounted compact downlight. Type II ( Asymmetrical Light Distribution) for 30W. Beam angle 15° / 24° / 40° for 25W & 40W. Luminaire made of extruded aluminium (grade 6063) Ø166 x 3mm thickness, pressure die-cast aluminium alloy of high corrosion resistance and external non corrosive stainless steel fasteners. Clear toughened glass of 4mm thickness. Aluminium plate for surface mounting on ceiling. Polycarbonate optical lens. Single cable entrance via PG9 cable gland. Protection class IP65. Mechanical resistance IK07. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70 for 30W & 2700K / 3000K / 4000K / 6500K, Colour rendering index (CRI)>90 for 25W & 40W K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : 166mm diameter x 175mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 2700K,3000K,4000K,5700K

Optics:

Mounting: Surface

Finish: RAL 9004 Black,RAL 9007 Grey aluminium, RAL 7016 Anthracite grey,Graphite grey