

Product Datasheet - 22544

Nebula Micro
ID : 22544
Input power : 3W LED
Technical Description
K-Lite Spike / Bracket / tilt mounted compact spot light designed to provide directional light. Beam angle 12° / 24° / 40°. Luminaire made of pressure die cast aluminium alloy of high corrosion resistance and non corrosive stainless steel fasteners. Clear toughened glass of 4mm thickness. Hybrid optical lens for higher efficiency, lower optical losses with optimum glare suppression. Surface mounting spike made of polypropylene black / Pressure die-cast aluminium surface mounting base. Swivel range of 0° - 90°. Single cable entrance M10 cable gland. Protection class IP66. Mechanical resistance IK07. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Luminaire dimension : Spike - 93mm length x 90mm width x 320mm height / Bracket- 93mm length x 64mm width x 83mm height / Tilt - 93mm length x 60mm width x 97mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 3

CCT: 2700K,3000K,4000K,5700K

Optics: 12°,24°,40°

Mounting:

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey