

Product Datasheet - 22547

Trioscape
ID : 22547
Input power : 6W / 12W LED
Technical Description
K-Lite surface mounted compact spot light designed to provide directional light. Beam angle 12° / 24° / 40°. Luminaire made of pressure die cast aluminium alloy of high corrosion resistance and external non corrosive stainless steel fasteners. Clear toughened glass of 4mm thickness. Polycarbonate optical lens. Surface mounting spike made of polypropylene black / Pressure die-cast aluminium surface mounting base. Swivel range of 0°- 90°. Single cable entrance M10 cable gland. Protection class IP65. Mechanical resistance IK06. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 6500K, Colour rendering index (CRI)>90. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Luminaire dimension : Spike - 110mm length x 106mm width x 447mm height & Bracket - 83mm length x 116mm width x 110mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Trioscape
ID : 22547
Holder :

GU10
Technical Description
K-Lite spike mounted compact spot light designed to provide directional light. Luminaire made of pressure die cast aluminium alloy of high corrosion resistance and non corrosive stainless steel fasteners, pressure die-cast aluminium glass fixing ring with clear toughened glass of 4mm thickness. Surface mounting spike made of polypropylene black / Pressure die-cast aluminium surface mounting base. Swivel range of 0°-90°. Single cable entrance M10 cable gland. Protection class IP65. Mechanical resistance IK06. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Prewired with GU10 holder and suitable for operating on 240V, 50Hz single phase ac supply. Luminaire dimension : Spike - 110mm length x 106mm width x 447mm height & Bracket - 83mm length x 116mm width x 110mm height.

Wattage:

CCT: 2700K,3000K,4000K,6500K

Optics: 12°,24°,40°

Mounting:

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey