

Product Datasheet - 22577

Acorn
ID : 22577
Input power : 30W / 50W LED
Technical Description
K-Lite pendant mounted compact street light. Type II (Asymmetrical light distribution). Decorative luminaire made of specially contoured spun aluminium body of high corrosion resistance and non corrosive stainless steel fasteners. Clear acrylic diffuser(A9). The mounting arrangement nipple, coupling & Hex nut made of Stainless steel 304 suitable for mounting to internally threaded pipe of designation M30. Protection class IP65. Mechanical resistance IK05. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey and Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 1,00,000 operating hours. Operating temperature range is from -15°C to +50°C. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 4KV / 6KV. Luminaire dimension : 312mm diameter x 382mm height. CE Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 2700K,3000K,4000K,5700K

Optics: Type II

Mounting: D4

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey