

Product Datasheet - 22784

Parula
ID : 22784
Input power : 1 x 6W LED
Technical Description
K-Lite Bollard luminaire designed for surface mounted. Symmetrical light distribution. Luminaire made of extruded aluminium tube (grade 6063), die-cast aluminium components of high corrosion resistance and external non corrosive stainless steel fasteners. Clear toughened glass. Tilttable : -45° to +45°. Die cast aluminium mounting base 60mm diameter with 2 holes 6.5mm diameter to suit coach screws at PCD 41 with cable entry hole 8.5mm diameter. Protection class IP64. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K. Colour rendering index (CRI)>80. Constant voltage non integral power supply at 24Vdc assures safety. Supplied with suitable external dc to dc converter, to be installed with suitable IP Junction box. Luminaire dimension : 90 x Ø60 x 500 / 700 / 900 mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 6

CCT: 2700K,3000K,4000K,5700K

Optics:

Mounting: M54

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey