

Product Datasheet - 23099

Polar High Bay 2
ID : 23099
Input power : 2 x 60W LED
Technical Description
K-Lite high efficiency industrial luminaire designed to provide uniform illumination in open spaces. Beam angle 25° / 40° / 60°. Extruded aluminium side frame, IP67 LED Module with excellent thermal management heat sink & polycarbonate optical lens. Mounting bracket made of CRCA sheet (3mm thickness). All external screws are made of stainless steel. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 3000K / 4000K / 5700K. Colour rendering index (CRI)>70. SDCM-3 MacAdam. K-Lite LED module with expected service life of at least 84,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >90%, Power factor >0.95, THD <6.5%, Surge protection 4KV. Luminaire dimension : 342mm length x 155mm width x 205mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 60

CCT: 3000K,4000K,5700K

Optics: 25°,40°,60°

Mounting: Bracket - Surface

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey