

Product Datasheet - 23613

Bema 7
ID : 3613
LED 3000K,4000K,6500K 240Vac CRI >80 MacAdam step 3
Input power : 22W
Dimension Ø177 x 43 mm
Beam Angle : 120°(Fixed)
Electronic driver ON/OFF
CE and BIS

LUMINAIRE TYPE
Wall Mounted luminaire. IP rating IP40
MATERIAL CHARACTERISTICS
Die-Cast aluminium body. Translucent Polystyrene diffuser.
Epoxy polyester powder coated process : Acid treatment & White epoxy polyester powder coating.
INSTALLATION AND MAINTENANCE
Ceiling surface mounting.
LIGHTING PERFORMANCE
Translucent Polystyrene diffuser for glare free, uniform light distribution
BEMA 7
This luminaire contains built-in LED modules. LED modules are engineered accordingly to the existing regulations of Lumen Maintenance (LM80) and Technical Memorandum (TM21), Lifespan of the luminaire 54,000 hours at 40°C. Operating ambient temperature range is from -15°C to +50°C. Driver efficiency >85%, power factor >0.9, THD <10%, Surge protection 2.5KV.

Wattage: 22

CCT: 3000K,4000K,6500K

Optics: 120°

Mounting: Ceiling Surface

Finish: White