

Product Datasheet - 23628

Cylin Mega
ID : 23628
Input power : 50W LED
Technical Description
K-Lite ceiling mounted compact downlight. Symmetrical & Type II (Asymmetrical light distribution). Luminaire made of extruded aluminium tube (grade 6063) Ø210mm, die-cast aluminium alloy of high corrosion resistance and non corrosive stainless steel fasteners. Clear toughened glass of 4mm thickness. Die cast aluminium plate for surface mounting on ceiling. Polycarbonate optical lens for higher efficiency, lower optical losses with optimum glare suppression. Single cable entrance via PG7 cable gland. Protection class IP65. Mechanical resistance IK05. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >88%, Power factor >0.95, THD <10%, Surge protection 6KV. Luminaire dimension : 210mm diameter x 140mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 50

CCT: 2700K,3000K,4000K,5700K

Optics: Symmetrical,Type II

Mounting: Surface

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey