

Product Datasheet - 24086

MINILED
ID : 24086
Input power : 3W / 5W LED
Technical Description
Compact IP67 LED fittings suitable for down light, Wall recessed and walkover for both indoor & outdoor applications with small dimension flush mounting installation. Beam angle 8° / 24° / 40°. These fixtures should be perfect for creating very defined effects of accent light. Luminaire body and screwless front ring made from solid billet of 316 grade stainless steel, ensuring IP67 rating silicone seal gasket, with clear / prismatic / opal / asymmetrical clear toughened glass 4mm thickness, polycarbonate optical lens. Luminaire must be hard wired with 2 x 0.5mm² cable of 0.5 metre length shall be supplied. Polypropylene mounting sleeve for preparing recessed opening in ground or wall. Protection class IP67. Mechanical resistance IK08. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Constant current non integral power supply. Luminaires to be ordered with suitable power supply. Suitable for operating on 240V, 50Hz single phase ac supply. Luminaire dimension : 39mm diameter x 67mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 2700K,3000K,4000K,5700K

Optics: 12° / 24° / 40°

Mounting: Recess

Finish: Stainless Steel