

Product Datasheet - 24211

Wall Jado
ID : 24211
Input power : 12W LED
Technical Description
K-Lite wall luminaire designed for wall mounting. Asymmetrical light distribution. Luminaire housing made of GI frame, Pressure die cast aluminium. Clear acrylic diffuser. Pressure die cast aluminium base for easy installation onto the wall. Mounting plate 109mm square x 10mm x 1mm thick with 4 holes Ø5 to suit coach screws at CC 90. All external screws are made of stainless steel. Protection class IP65. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Special finish teak / bamboo on request. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >80%, Power factor >0.95, THD <10%, Surge protection 3KV. Luminaire dimension : 205mm length x 86mm width x 251mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 12

CCT: 2700K,3000K,4000K,5700K

Optics:

Mounting: W28

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey