

Product Datasheet - 24329

Vela 2.0
ID : 24329
Input power : 50W LED
Technical Description
K-Lite recessed ceiling mounted compact downlight. Beam angle 10° / 28° / 45°. Luminaire made of die-cast aluminium with heat sink for excellent thermal management. Polycarbonate optical lens for higher efficiency, lower optical losses with optimum glare suppression. Protection class IP66 for LED module. Mechanical resistance IK10. Silicone compression gasket. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, RAL 9016 Traffic white, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 6KV. Luminaire dimension : 184mm diameter x 88mm height. C.O.D : 170mm diameter. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 50

CCT: 2700K,3000K,4000K,5700K

Optics: 10°,28°,45°

Mounting: Recess

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,RAL 9016 Traffic White,Graphite Grey