

Product Datasheet - 24372

Kayal Mini
ID : 24372
Input power : 30W LED
Technical Description
K-Lite Pole top luminaire. Type II (Asymmetrical light distribution). Luminaire made of extruded aluminium alloy (grade 6063) with die cast aluminium components of high corrosion resistance. Toughened glass of 4mm thickness. Extruded aluminium base suitable for mounting 76mm & 88.9mm OD pole. All external screws are made of stainless steel. Protection class IP65. Mechanical resistance IK08. Pure polyester powder coated RAL9004 Black, RAL9007 Grey aluminium, RAL7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 72,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : 308mm / 319mm length x Ø166mm width x 260mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 30

CCT: 2700K,3000K,4000K,5700K

Optics: Type II

Mounting: D3,D26

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey