

Product Datasheet - 24379

Cyrilla Round - Post Top
ID : 24379
Input power : 30W LED
Technical Description
K-Lite pole-top luminaire. Symmetrical light distribution. Luminaire top cover & bottom frame with decorative embellishment made of die-cast aluminium. Extruded aluminium supporting arm(grade 6063). Clear polycarbonate diffuser. Die cast aluminium base suitable for mounting on Ø50mm OD pipe.. All external screws are made of stainless steel. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : 221mm diameter x 600mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 30

CCT: 2700K,3000K,4000K,5700K

Optics: Symmetrical

Mounting: D1

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey