

Product Datasheet - 24396

Aariya
ID : 24396
Input power : 30W / 50W LED
Technical Description
K-Lite pendant mounted compact street light. Symmetrical / Asymmetrical light distribution (Type II / Type III / Type IV). Decorative luminaire made of spun aluminium body and external non corrosive stainless steel fasteners. Clear acrylic diffuser. The mounting arrangement nipple, coupling & Hex nut made of Stainless steel 304 suitable for mounting to internally threaded pipe of designation M30. Protection class IP65. Mechanical resistance IK07. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 1,00,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 4KV / 6KV. Luminaire dimension : 400mm diameter x 153mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 3000K,4000K,5700K

Optics: Symmetrical / Type II, III, IV

Mounting: D4

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey