

Product Datasheet - 24399

Vimana
ID : 24399
Input power : 50W LED
Technical Description
K-Lite Pole top luminaire. Symmetrical light distribution. Luminaire made of spun aluminium of high corrosion resistance. Clear Polycarbonate diffuser. Extruded aluminium alloy (grade6063) suitable for mounting 76mm OD pole. All external screws are made of stainless steel. Protection class IP65. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 1,00,000 operating hours. Operating within temperature range from - 15°C to + 50°C. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.9, THD <10%, Surge protection 6KV. Luminaire dimension : 566mm diameter x 500mm height. CE Certified. Inhouse NABL accredited lab.

Wattage: 50

CCT: 2700K,3000K,4000K,5700K

Optics:

Mounting: D3

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey