

Product Datasheet - 24454

Ezhil 2.0
ID : 24454
Input power : 30W / 50W LED
Technical Description
K-Lite Pole top luminaire. Type III (Asymmetrical light distribution). Luminaire made of Extruded aluminium alloy (grade 6063) of high corrosion resistance. Polycarbonate optical lens. Extruded aluminium base suitable for mounting 91mm square pole. All external screws are made of stainless steel. Protection class IP65 for LED Module. Mechanical resistance IK09. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey. Available colour temperature 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 4KV / 6KV. Luminaire dimension : 740mm length x 120mm width x 994mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 30W,50

CCT: 3000K,4000K,5700K

Optics: Type III

Mounting: D16

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey