

Product Datasheet - 24465

Rado-X
ID : 24465
Input power : 12W / 24W LED
Technical Description
K-Lite Wall-mounted compact downlight. Asymmetrical / Type II. Luminaire body made of pressure die cast aluminium of high corrosion resistance. Polycarbonate optical lens & reflector. Clear toughened glass of 4mm thickness. Cable entrance via M10 cable gland. Adjustable bracket made of pressure die cast aluminium. Pressure die cast aluminium base for surface mounting on wall. All external screws are made of stainless steel. Protection class IP65. Mechanical resistance IK07. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)90 / 80 . K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : 294mm length x 124mm width x 100mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 2700K,3000K,4000K,6500K

Optics: Asymmetrical, Type II

Mounting: W41

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey