

Product Datasheet - 24467

Navi Midi Spot
ID : 24467
Input power : 90W
Technical Description
K-Lite compact and robust flood light luminaire designed to provide uniform illumination in open spaces. Beam angle 6°. Luminaire made of pressure die cast aluminium of high corrosion resistance with extruded aluminium alloy tube (grade 6063). Clear toughened glass. Adjustable bracket made of stainless steel (3mm thickness) to facilitate proper aiming of the luminaire at desired angle. Pressure die cast aluminium mounting plate Ø100.5 x 4mm thick with 2 elongated holes 15 x 10 to suit M8 bolts at PCD 55 with pure polyester powder coating. This mounting plate along with foundation bolts of suitable size to be used for ensuring firm grouting into the specially designed foundation. Cable entrance via PG11 cable gland. All external screws are made of stainless steel. Protection class IP65. Mechanical resistance IK07. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD< 10%, Surge protection 6KV. Luminaire dimension : 249mm length x 123mm width x 567mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 90

CCT: 2700K,3000K,4000K,5700K

Optics: 6°

Mounting: M2

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey