

Product Datasheet - 24520

Gema
ID : 24520
Input power : 30W LED
Technical Description
K-Lite pole top luminaire. Symmetrical light distribution. Luminaire made of spun aluminium top cover, extruded aluminium (grade 6063) pipe with pressure die cast aluminium mounting base and non corrosive stainless steel fasteners. Inner aluminium reflector is profiled for improved illumination efficiency. Clear acrylic diffuser. Pressure die cast aluminium base suitable for mounting on Ø60mm OD pipe. Protection class IP65. Mechanical resistance IK06. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >88%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : 590mm diameter x 520mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 30

CCT: 2700K,3000K,4000K,5700K

Optics:

Mounting: D2

Finish: RAL 9004 Black,RAL 9007 Grey aluminium, RAL 7016 Anthracite grey,Graphite grey