

Product Datasheet - 24553

Stix Light
ID : 24553
Input power : 3 x 3W LED
Technical Description
K-Lite Bollard luminaire designed for surface mounted. Symmetrical light distribution. Luminaire made of extruded aluminium tube and external non corrosive stainless steel fasteners. Clear acrylic rod. Extruded aluminium mounting base & Pressure die cast aluminium mounting plate 167mm diameter x 4mm thick with 4 elongated holes 20 x 14 to suit M12 bolts at PCD 110 with pure polyester powder coating. This mounting plate along with foundation bolts of suitable size to be used for ensuring firm grouting into the specially designed foundation. Protection class IP65. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey (Special finish on request - Teak / Bamboo). Available colour temperature 2700K / 3000K / 4000K / 5700K (Special CCT on Request- Amber / Red / Greed / Blue). Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Power factor >0.9, THD <10%, Surge protection 2KV. Luminaire dimension : 247mm length x 255mm width x 1289mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 3

CCT: 2700K,3000K,4000K,5700K

Optics:

Mounting: M3

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey