

Product Datasheet - 24572

Vista Bollard
ID : 24572
Input power : 24W LED
Technical Description
K-Lite Bollard luminaire designed for surface mounted. Symmetrical light distribution. Luminaire made of extruded aluminium (grade 6063), spun aluminium components and non corrosive stainless steel fasteners. Translucent polycarbonate diffuser. Pressure die cast aluminium mounting plate 167mm diameter x 4mm thick with 4 elongated holes 20 x 14 to suit M12 bolts at PCD 110 for surface mounting on floor. The base plate have a cable entry hole of 75mm dia at the center. Protection class IP65. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K. Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.9, THD <10%, Surge protection 4KV. Luminaire dimension : 250mm diameter x 900mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 24

CCT: 2700K,3000K,4000K,5700K

Optics:

Mounting: M3

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey