

## Product Datasheet - 25380

Juno Midi<br>ID : 25380<br>Input power : 36W LED<br>Technical Description<br>K-Lite pole top luminaire. Beam angle 120°. Luminaire made of spun aluminium, integrated with extruded aluminium pipe along with pressure die cast aluminium base through supporting arms made fo gravity die cast aluminium and non corrosive stainless steel fasteners. Diffuser placed into the provision formed on the pheriphery of the bottom cover. Translucent acrylic diffuser. Suitable for mounting on Ø50mm OD pipe. Protection class IP65. Mechanical resistance IK07. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : 420mm diameter x 430mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 36

CCT: 2700K,3000K,4000K,5700K

Optics: 120°

Mounting: D1

Finish: RAL 9004 Black,RAL 9007 Grey aluminium, RAL 7016 Anthracite grey,Graphite grey